CASE WHEELED LOADERS 521D CASE 445TA/M2 (2003-2005)



ENGINE Case 445TA/M2 Capacity: 12,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT AND REAR Capacity: 22 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Unigear LS GL-3/GL-5 85W-140	
<u> </u>	

Change every 1000 hours

HUB REDUCTIONS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Unigear LS GL-3/GL-5 85W-140	

Change every 1000 hours

TRANSMISSION POWERSHIFT ZF 4/3 Capacity: 18,9 liter (Change capacity), Capacity: 25,6 liter (Dry fill)			
	CLIMATE		
	Moderate		
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
	PRODUCT RECOMMENDATION 2		

Change every 1000 hours

HYDRAULIC SYSTEM Capacity: 57 liter (Hydraulic tank), Capacity: 114 liter (Total)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT-Plus			
Check even 50 hours, change even 2000 hours			

Check every 50 hours, change every 2000 hours

CASE WHEELED LOADERS 521D CASE 445TA/M2 (2003-2005)



GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

Change every 50 hours

COOLING SYSTEM Capacity: 22 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 10 hours, change every	2000 hours/ 12 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.