

CASE WHEELED LOADERS 621BXT CASE 6T-590 (1994-1999)



ENGINE Case 6T-830
Capacity: 15,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 250 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Asyntho 5W-30	Armado Synth 5W-30

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT
Capacity: 8,5 liter, Capacity: 1 liter (LS-additive)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 1000 hours

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 100 hours

DIFFERENTIAL REAR
Capacity: 8,5 liter, Capacity: 1 liter (LS-additive)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 1000 hours

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 100 hours

CASE WHEELED LOADERS 621BXT CASE 6T-590 (1994-1999)



HUB REDUCTIONS

Capacity: 5,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 1000 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 100 hours*

TRANSMISSION POWERSHIFT ZF 4WG150 4/3

Capacity: 7,6 liter (Change capacity), Capacity: 18,9 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40*Change every 1000 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Change every 1000 hours*

HYDRAULIC SYSTEM

Capacity: 90 liter (Hydraulic tank), Capacity: 153 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3

Agrifluid HT*Check every 50 hours, change every 2000 hours*

CASE WHEELED LOADERS 621BXT CASE 6T-590 (1994-1999)



COOLING SYSTEM

Capacity: 28 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.