

CASE WHEELED LOADERS 621F XT FPT FAHFE613Z TIER 4I/STAGE IIIB (2011-2016)

**ENGINE** FPT F4HFE613Z

Capacity: 13,25 liter (Change capacity), Capacity: 15,1 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 2

Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 3

Agridiesel MSP 15W-40*Check every 10 hours, change every 500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 2

Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 3

Agridiesel MSP 15W-40*Change every 100 hours***DIFFERENTIAL FRONT** ZF MT-L3075-II

Capacity: 22 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR ZF MT-L3065-II

Capacity: 22 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION POWERSHIFT ZF 4WG130 4/3

Capacity: 27 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3

Agrifluid HT*Check every 50 hours, change every 1000 hours*

USE	CLIMATE
Severe (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3

Agrifluid HT*Check every 50 hours, change every 500 hours*

CASE WHEELED LOADERS 621F XT FPT FAHFE613Z TIER 4I/STAGE IIIB (2011-2016)



HYDRAULIC SYSTEM

Capacity: 148 liter (System), Capacity: 91 liter (Tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Check every 50 hours, change every 2000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM

Capacity: 28,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 50 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.