

CASE MINI EXCAVATORS CK/CX CK08

**ENGINE** Kubota

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 20W-50	Multifleet SCD 40	Multifleet SCD 30

Change every 100 hours/ 6 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Change every 100 hours/ 6 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		

Change every 100 hours/ 6 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 100 hours/ 6 months

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 20W-50	Multifleet SCD 40	Multifleet SCD 30

Change every 50 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Change every 50 hours

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		

Change every 50 hours

CASE MINI EXCAVATORS CK/CX CK08



USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
<i>Change every 50 hours</i>		

HYDRAULIC SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
<i>Change every 1000 hours</i>		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

SWING REDUCTION UNIT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 1000 hours</i>		

SWING RING GEAR TEETH		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

TRACK ROLLERS + IDLER WHEELS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

CASE MINI EXCAVATORS CK/CX CK08



TRAVEL REDUCTION UNIT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 1000 hours</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.