

CASE MINI EXCAVATORS CK/CX CX18B SERIES 2 MITSUBISHI L3E (2008-2017)



ENGINE Mitsubishi L3E
Capacity: 3,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

Check every 10 hours, change every 250 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 9 liter (Hydraulic tank), Capacity: 24 liter (System)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Perlus Biosynth 46

PRODUCT RECOMMENDATION 2
Perlus H 46

Check every 250 hours, change every 2000 hours

GREASE POINTS/NIPPLES

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Q7 MP Calcep Grease WR 2

PRODUCT RECOMMENDATION 2
Caliplex HD Grease EP 2

PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2

Change every 10 hours

COOLING SYSTEM

Capacity: 3,7 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Coolant SP 15+

PRODUCT RECOMMENDATION 2
Coolant SP 12

Check every 10 hours, change every 1000 hours/ 24 months

SWING RING GEAR TEETH

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Q7 MP Calcep Grease WR 2

PRODUCT RECOMMENDATION 2
Caliplex HD Grease EP 2

PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2

Change every 50 hours

CASE MINI EXCAVATORS CK/CX CX18B SERIES 2 MITSUBISHI L3E (2008-2017)



TRACK ROLLERS + IDLER WHEELS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

TRAVEL REDUCTION UNIT

Capacity: 0,33 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.