

# CATERPILLAR ASPHALT PAVERS AP/BG

## AP-900B AGJ

**ENGINE**

Capacity: 20 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 2****Dieselfleet CD+ 15W-40****PRODUCT RECOMMENDATION 3****Multifleet SHPD 15W-40***Change every 250 hours/ 1 months***USE**

Normal

**CLIMATE**

Cold

**PRODUCT RECOMMENDATION 1****Synfleet SHPD 10W-40****PRODUCT RECOMMENDATION 2****Multifleet SHPD 10W-40***Change every 250 hours/ 1 months***HUB REDUCTIONS**

Capacity: 2,8 liter (each hub)

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Gearlube GL-5 85W-140****PRODUCT RECOMMENDATION 2****Unigear LS GL-3/GL-5 85W-140***Change every 500 hours/ 3 months***HYDRAULIC SYSTEM**

Capacity: 189 liter

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Gear Oil Alcat 30***Change every 1000 hours/ 12 months***USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gear Oil Alcat 10W****PRODUCT RECOMMENDATION 2****Perlus Biosynth 46***Change every 1000 hours/ 12 months*

# CATERPILLAR ASPHALT PAVERS AP/BG

## AP-900B AGJ



### COOLING SYSTEM

Capacity: 37 liter

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 17</b>		

*Change every 6000 hours/ 72 months*

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Change every 24 months/ 3000 hours*

### PUMP DRIVE UNIT

Capacity: 2,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1000 hours/ 12 months*

### REDUCTION UNITS AUGER ASSEMBLY AND CONVEYOR(S)

Capacity: 0,65-1 liter (each side)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

*Change every 500 hours/ 3 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.