## CATERPILLAR ARTICULATED DUMP TRUCKS 740 TIER 3 WWD (2008 AND AFTER)



ENGINE C15 Acert Capacity: 40 liter		
USE		CLIMATE
Preferred		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every	500 hours	
USF		CLIMATE

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	

Check every 10 hours, change every 500 hours

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 500 hours

use Alternative (acceptable)		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40

Check every 10 hours, change every 500 hours

<b>DIFFERENTIAL FRONT</b> Capacity: 66 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	

Check every 500 hours, change every 2000 hours

DIFFERENTIAL REAR LEADING Capacity: 67 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 500 hours, change every 2000 hours		

## CATERPILLAR ARTICULATED DUMP TRUCKS 740 TIER 3 WWD (2008 AND AFTER)



<b>DIFFERENTIAL REAR TRAILING</b> Capacity: 67 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Chack every 500 hours, change every 200	n hours	

Gear Oil Alcat 50

Check every 500 hours, change every 2000 hours

TRANSFERBOX Capacity: 18 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Check every 50 hours, change ever	1000 hours

TRANSMISSION + TORQUE CONVERTER Capacity: 72 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 50 hours, change every 1000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 50 hours, change every 1000 hours		

## CATERPILLAR ARTICULATED DUMP TRUCKS 740 TIER 3 WWD (2008 AND AFTER)



COOLING SYSTEM Capacity: 80 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	
Change every 6000 hours	

HYDRAULIC SYSTEM STEERING - Capacity: 233 liter	- BRAKES	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 500 hours, change eve	1/ 4000 hours	

Check every 500 hours, change every 4000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.