

CATERPILLAR UNDERGROUND ARTICULATED TRUCKS AD55 DNW (2004- 2011)



ENGINE C18 Acert MEUI
Capacity: 64 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40

Check every 10 hours, change every 1 months/ 250 hours

DIFFERENTIAL FRONT

Capacity: 138 liter (+ hub reductions)

USE
Alternative (acceptable)

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE
Initial service (alternative)

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50

Change every 500 hours

DIFFERENTIAL REAR

Capacity: 138 liter (+ hub reductions)

USE
Alternative (acceptable)

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE
Initial service (alternative)

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50

Change every 500 hours

CATERPILLAR UNDERGROUND ARTICULATED TRUCKS AD55 DNW (2004- 2011)

**TRANSMISSION**

Capacity: 53 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

Check every 10 hours, change every 6 months/ 1000 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 10 hours, change every 6 months/ 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 10 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM

Capacity: 258 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 10 hours, change every 6 months/ 1000 hours

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

CATERPILLAR UNDERGROUND ARTICULATED TRUCKS AD55 DNW (2004- 2011)

**COOLING SYSTEM**

Capacity: 75 liter

USE		CLIMATE
Preferred, extended		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 10 hours, change every 48 months/ 6000 hours

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 24 months/ 3000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.