

# CATERPILLAR RIGID DUMP TRUCKS 770G

## (2014 AND AFTER)



**ENGINE** C15 Acert  
Capacity: 40 liter

USE	CLIMATE
Preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agridiesel MSP 15W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth MSP 5W-40</b>	<b>Dieselfleet LSP Ultra 10W-30</b>	<b>Dieselfleet MSP 10W-30</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agrisynth MSP 10W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agridiesel MSP 15W-40</b>	<b>Armado Synth LSP Ultra 10W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

### DIFFERENTIAL REAR

Capacity: 114 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

### HUB REDUCTIONS REAR

Capacity: 22,5 liter (each)

We are unable to give a standard recommendation for this component. Please contact our service department.

# CATERPILLAR RIGID DUMP TRUCKS 770G (2014 AND AFTER)



## TRANSMISSION + TORQUE CONVERTER

Capacity: 95 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 10 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 10 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Fluid analysis	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 500 hours*

USE	CLIMATE
Fluid analysis	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 500 hours*

## HYDRAULIC SYSTEM HOIST + BRAKE

Capacity: 178 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 10 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Fluid analysis	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 500 hours*

# CATERPILLAR RIGID DUMP TRUCKS 770G (2014 AND AFTER)



## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

USE	CLIMATE
Light Duty	Moderate

PRODUCT RECOMMENDATION 1

**HT Q9 High Grade Grease**

PRODUCT RECOMMENDATION 2

**Labora Grease**

## WHEEL BEARINGS FRONT

Capacity: 2,5 liter (each)

We are unable to give a standard recommendation for this component. Please contact our service department.

## COOLING SYSTEM

Capacity: 132 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 17**

*Check every 10 hours, change every 36 months/ 6000 hours*

# CATERPILLAR RIGID DUMP TRUCKS 770G (2014 AND AFTER)



## HYDRAULIC SYSTEM STEERING

Capacity: 68 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

Check every 10 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Agrifluid Synth XHP Ultra</b>

Check every 10 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Fluid analysis		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

Check every 500 hours

USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Agrifluid Synth XHP Ultra</b>

Check every 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.