

CATERPILLAR RIGID DUMP TRUCKS 773D

NBJ (1996-2001)



ENGINE 3412E
Capacity: 76 liter

| USE | CLIMATE |
|----------------------|---------------|
| Extended drain (max) | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|------------------------------|-------------------------------|
| Agridiesel MSP 15W-40 | Dieselfleet MSP 15W-40 |

Check every 10 hours, change every 1 months/ 250 hours

| USE | CLIMATE |
|----------------------|----------|
| Extended drain (max) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------------|-------------------------------|
| Armado Synth MSP 5W-40 | Dieselfleet LSP Ultra 10W-30 | Dieselfleet MSP 10W-30 |

Check every 10 hours, change every 1 months/ 250 hours

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-----------------------------|-------------------------------|
| Agrisynth MSP 10W-40 | Dieselfleet MSP 15W-40 |

Check every 10 hours, change every 1 months/ 250 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------------|------------------------------|--------------------------------------|
| Agrisynth LSP Ultra 10W-40 | Agridiesel MSP 15W-40 | Armado Synth LSP Ultra 10W-40 |

Check every 10 hours, change every 1 months/ 250 hours

DIFFERENTIAL REAR

Capacity: 140 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION + TORQUE CONVERTER

Capacity: 53 liter, Capacity: 96 liter (Complete)

| USE | CLIMATE |
|----------------|---------------|
| Flexible (max) | Mediterranean |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| Gear Oil Alcat 30 | |

Check every 10 hours, change every 6 months/ 1000 hours

| USE | CLIMATE |
|----------------|---------|
| Flexible (max) | Cold |

| PRODUCT RECOMMENDATION 1 | |
|---------------------------|--|
| Gear Oil Alcat 10W | |

Check every 10 hours, change every 6 months/ 1000 hours

CATERPILLAR RIGID DUMP TRUCKS 773D

NBJ (1996-2001)



HYDRAULIC SYSTEM HOIST + BRAKE

Capacity: 133 liter (Hydraulic tank), Capacity: 375 liter (Total)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 10 hours, change every 6 months/ 1000 hours*

CENTRAL LUBRICATION SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

FAN DRIVE BEARINGS

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

| USE | CLIMATE |
|------------|----------|
| Light Duty | Moderate |

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease

WHEEL BEARINGS FRONT

Capacity: 3,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 137 liter

| USE | CLIMATE |
|----------|----------|
| Extended | Moderate |

PRODUCT RECOMMENDATION 1

Coolant SP 17*Check every 10 hours, change every 24 months/ 3000 hours*

CATERPILLAR RIGID DUMP TRUCKS 773D NBJ (1996-2001)


POWER STEERING HYDRAULIC SYSTEM

Capacity: 34 liter (Hydraulic tank), Capacity: 58 liter (Total)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 10 hours, change every 6 months/ 1000 hours*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30*Check every 10 hours, change every 6 months/ 1000 hours*

| USE | CLIMATE |
|-------------------|----------|
| Biodegradable oil | Moderate |

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46*Check every 10 hours, change every 6 months/ 1000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.