

# CATERPILLAR BULLDOZERS/TRACKED TRACTORS D3K LGP (2006-2012)



**ENGINE** C4.4 Acert  
Capacity: 11 liter

USE	CLIMATE
Preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agridiesel MSP 15W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Armado Synth LSP Ultra 10W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agrisynth LSP 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	
<b>Dieselfleet MSP 15W-40</b>	

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

# CATERPILLAR BULLDOZERS/TRACKED TRACTORS D3K LGP (2006-2012)



## HYDRAULIC SYSTEM

Capacity: 60 liter (Hydraulic tank), Capacity: 84 liter (System)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>AgriDiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

Check every 10 hours, change every 2000 hours/ 12 months

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

## COOLING SYSTEM

Capacity: 22,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 17</b>		

Check every 10 hours, change every 72 months/ 6000 hours

## TRAVEL REDUCTION UNIT

Capacity: 8,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

# CATERPILLAR BULLDOZERS/TRACKED TRACTORS D3K LGP (2006-2012)

**WINCH**

Capacity: 4,7 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

Check every 1 months/ 250 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

Check every 1 months/ 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.