

# CATERPILLAR WHEELED LOADERS 906 6ZS/CATERPILLAR 3034 (1998-2004)



**ENGINE** 3034  
Capacity: 7 liter

| USE       | CLIMATE       |
|-----------|---------------|
| Preferred | Mediterranean |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      |
|------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Dieselfleet MSP 15W-40</b> |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE       | CLIMATE  |
|-----------|----------|
| Preferred | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2          | PRODUCT RECOMMENDATION 3    |
|-------------------------------------|-----------------------------------|-----------------------------|
| <b>Agrisynth LSP Ultra FE 5W-30</b> | <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth MSP 10W-40</b> |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      |
|-----------------------------|-------------------------------|
| <b>Agrisynth LSP 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE                      | CLIMATE       |
|--------------------------|---------------|
| Alternative (acceptable) | Mediterranean |

| PRODUCT RECOMMENDATION 1      |  |
|-------------------------------|--|
| <b>Dieselfleet MSP 15W-40</b> |  |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE                      | CLIMATE  |
|--------------------------|----------|
| Alternative (acceptable) | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2          | PRODUCT RECOMMENDATION 3    |
|-------------------------------------|-----------------------------------|-----------------------------|
| <b>Agrisynth LSP Ultra FE 5W-30</b> | <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth MSP 10W-40</b> |

*Check every 10 hours, change every 500 hours/ 12 months*

## DIFFERENTIAL FRONT

Capacity: 7,5 liter, Capacity: 0,5 liter (LS-additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

# CATERPILLAR WHEELED LOADERS 906 6ZS/CATERPILLAR 3034 (1998-2004)



## DIFFERENTIAL REAR LIMITED SLIP

Capacity: 7,5 liter, Capacity: 0,5 liter (LS-additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

## HUB REDUCTIONS FRONT

Capacity: 0,7 liter

| USE                          |                                     | CLIMATE       |
|------------------------------|-------------------------------------|---------------|
| Normal                       |                                     | Mediterranean |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |               |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |               |

*Check every 6 months/ 250 hours, change every 12 months/ 1000 hours*

| USE                            |                          | CLIMATE                   |
|--------------------------------|--------------------------|---------------------------|
| Normal                         |                          | Moderate                  |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
| <b>Gearlube Racing 75W-140</b> | <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |

*Check every 6 months/ 250 hours, change every 12 months/ 1000 hours*

## HUB REDUCTIONS REAR

Capacity: 0,7 liter

| USE                          |                                     | CLIMATE       |
|------------------------------|-------------------------------------|---------------|
| Normal                       |                                     | Mediterranean |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |               |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |               |

*Check every 6 months/ 250 hours, change every 12 months/ 1000 hours*

| USE                            |                          | CLIMATE                   |
|--------------------------------|--------------------------|---------------------------|
| Normal                         |                          | Moderate                  |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
| <b>Gearlube Racing 75W-140</b> | <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |

*Check every 6 months/ 250 hours, change every 12 months/ 1000 hours*

## TRANSMISSION HYDROSTATIC

Capacity: 1,4 liter

| USE                           |                               | CLIMATE                       |
|-------------------------------|-------------------------------|-------------------------------|
| Normal                        |                               | Moderate                      |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Check every 6 months/ 250 hours, change every 12 months/ 1000 hours*

# CATERPILLAR WHEELED LOADERS 906

## 6ZS/CATERPILLAR 3034 (1998-2004)



### HYDRAULIC SYSTEM

Capacity: 49 liter (Hydraulic tank)

| USE                           |                               | CLIMATE                       |
|-------------------------------|-------------------------------|-------------------------------|
| Normal                        |                               | Moderate                      |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Check every 10 hours, change every 2000 hours/ 12 months

### COOLING SYSTEM

Capacity: 14 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 17</b>     |  |          |

Check every 10 hours, change every 48 months/ 6000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.