

# CATERPILLAR WHEELED LOADERS 906H2

## JRF/CATERPILLAR C3.3B DIT TIER 4I (2012 AND AFTER)



**ENGINE** C3.3B DIT Tier 4i  
Capacity: 10 liter

| USE       | CLIMATE       |
|-----------|---------------|
| Preferred | Mediterranean |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      |
|------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Dieselfleet MSP 15W-40</b> |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE       | CLIMATE  |
|-----------|----------|
| Preferred | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2      |
|-------------------------------------|-------------------------------|
| <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE                      | CLIMATE       |
|--------------------------|---------------|
| Alternative (acceptable) | Mediterranean |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      |
|-----------------------------|-------------------------------|
| <b>Agrisynth MSP 10W-40</b> | <b>Dieselfleet MSP 15W-40</b> |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE                      | CLIMATE  |
|--------------------------|----------|
| Alternative (acceptable) | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2     | PRODUCT RECOMMENDATION 3            |
|-------------------------------------|------------------------------|-------------------------------------|
| <b>Agrisynth LSP Ultra FE 5W-30</b> | <b>Agridiesel MSP 15W-40</b> | <b>Dieselfleet LSP Ultra 10W-30</b> |

*Check every 10 hours, change every 500 hours/ 12 months*

**DIFFERENTIAL FRONT**  
Capacity: 8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |
|--------------------------|--|
| <b>Gear Oil Alcat 30</b> |  |

**DIFFERENTIAL REAR**  
Capacity: 8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |
|--------------------------|--|
| <b>Gear Oil Alcat 30</b> |  |

# CATERPILLAR WHEELED LOADERS 906H2

## JRF/CATERPILLAR C3.3B DIT TIER 4I (2012 AND AFTER)

**HUB REDUCTIONS FRONT**

Capacity: 0,8 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Gear Oil Alcat 30</b> |  |          |

**HUB REDUCTIONS REAR**

Capacity: 0,8 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Gear Oil Alcat 30</b> |  |          |

**TRANSMISSION HYDROSTATIC**

Capacity: 1,3 liter, Capacity: 1,25 liter ("speeder" version)

| USE                      |                          | CLIMATE       |
|--------------------------|--------------------------|---------------|
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| <b>Gear Oil Alcat 30</b> | <b>Gear Oil Alcat 50</b> |               |

*Check every 250 hours, change every 6 months/ 1000 hours*

| USE                       |  | CLIMATE |
|---------------------------|--|---------|
| Normal                    |  | Cold    |
| PRODUCT RECOMMENDATION 1  |  |         |
| <b>Gear Oil Alcat 10W</b> |  |         |

*Check every 250 hours, change every 6 months/ 1000 hours***HYDRAULIC SYSTEM**

Capacity: 84 liter (Hydraulic tank)

| USE                      |                          | CLIMATE       |
|--------------------------|--------------------------|---------------|
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| <b>Multifleet SCD 30</b> | <b>Gear Oil Alcat 30</b> |               |

*Check every 10 hours, change every 2000 hours/ 12 months*

| USE                           |                          | CLIMATE                     |
|-------------------------------|--------------------------|-----------------------------|
| Normal                        |                          | Moderate                    |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3    |
| <b>AgriDiesel CRD+ 15W-40</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

*Check every 10 hours, change every 2000 hours/ 12 months*

# CATERPILLAR WHEELED LOADERS 906H2 JRF/CATERPILLAR C3.3B DIT TIER 4I (2012 AND AFTER)



## HYDRAULIC BRAKE SYSTEM STANDARD DRIVE

Capacity: 0,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 10 hours, change every 1000 hours/ 12 months*

## GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

## COOLING SYSTEM

Capacity: 24 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 17***Check every 10 hours, change every 48 months/ 6000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.