

# CATERPILLAR VIBRATORY COMPACTORS

## CB/CC/CD/CP/CS CB-534D FEA (2005 AND AFTER)



**ENGINE** Caterpillar 3054C  
Capacity: 9 liter

| USE                           |                               | CLIMATE                       |
|-------------------------------|-------------------------------|-------------------------------|
| Normal                        |                               | Mediterranean                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Check every 10 hours, change every 500 hours/ 6 months*

| USE                         |                               | CLIMATE  |
|-----------------------------|-------------------------------|----------|
| Normal                      |                               | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      |          |
| <b>Agrisynth LSP 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |          |

*Check every 10 hours, change every 500 hours/ 6 months*

**HYDRAULIC SYSTEM**  
Capacity: 60 liter (Hydraulic tank)

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Gear Oil Alcat 30</b> |  |               |

*Check every 10 hours, change every 1000 hours/ 12 months*

| USE                           |                          | CLIMATE                     |
|-------------------------------|--------------------------|-----------------------------|
| Normal                        |                          | Moderate                    |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3    |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

*Check every 10 hours, change every 1000 hours/ 12 months*

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Biodegradable oil         |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Perlus Biosynth 46</b> |  |          |

*Check every 10 hours, change every 1000 hours/ 12 months*

### GREASE POINTS/NIPPLES

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

# CATERPILLAR VIBRATORY COMPACTORS

## CB/CC/CD/CP/CS CB-534D FEA (2005 AND AFTER)

**COOLING SYSTEM**

Capacity: 18 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 17</b>     |  |          |

*Check every 10 hours, change every 36 months/ 6000 hours*

**ECCENTRIC WEIGHT HOUSING**

Capacity: 11,8 liter (each)

| USE                            |                                 | CLIMATE  |
|--------------------------------|---------------------------------|----------|
| Normal                         |                                 | Moderate |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2        |          |
| <b>Gearlube Racing 75W-140</b> | <b>Gearlube HS GL-5 80W-140</b> |          |

*Check every 3 months/ 250 hours, change every 36 months/ 3000 hours*

**ECCENTRIC WEIGHT HOUSING** Versa Vibe

Capacity: 9 liter (each)

| USE                            |                                 | CLIMATE  |
|--------------------------------|---------------------------------|----------|
| Normal                         |                                 | Moderate |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2        |          |
| <b>Gearlube Racing 75W-140</b> | <b>Gearlube HS GL-5 80W-140</b> |          |

*Check every 3 months/ 250 hours, change every 36 months/ 3000 hours*

**PLANETARY DRUM DRIVE**

Capacity: 2,4 liter

| USE                            |                                 | CLIMATE  |
|--------------------------------|---------------------------------|----------|
| Normal                         |                                 | Moderate |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2        |          |
| <b>Gearlube Racing 75W-140</b> | <b>Gearlube HS GL-5 80W-140</b> |          |

*Check every 3 months/ 250 hours, change every 1000 hours*

| USE                            |                                 | CLIMATE  |
|--------------------------------|---------------------------------|----------|
| Initial service                |                                 | Moderate |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2        |          |
| <b>Gearlube Racing 75W-140</b> | <b>Gearlube HS GL-5 80W-140</b> |          |

*Change every 250 hours/ 6 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.