Check every 10 hours, change every 250 hours/3 months

## **CATERPILLAR VIBRATORY COMPACTORS** CB/CC/CD/CP/CS CP-563C 4LN00807 ->



(1995-2000)

ENGINE 3116T Capacity: 20 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every 250	hours/ 3 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

TRANSAXLE Capacity: 27 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 3 months/ 250 hours.	change every 12 months/ 1000 hours	'

HYDRAULIC SYSTEM Capacity: 110 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Check every 10 hours, change every 1000 hours/ 12 months		

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 10 hours, change every 1000	) hours/ 12 months	

KROON-OIL B.V. Postbus 149 7600 AC Almelo

Dollegoorweg 15

7602 EC Almelo

## CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CP-563C 4LN00807 ->



(1995-2000)

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
USE	CLIMATE
use Light Duty	climate Moderate
Light Duty	Moderate

COOLING SYSTEM Capacity: 33,1 liter	
USE	CLIMATE
Preferred, extended	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	

Check every 10 hours, change every 72 months/ 6000 hours

Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE

Check every 10 hours, change every 24 months/ 3000 hours

PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
	Moderate
	CLIMATE
Gear Oil Alcat 30	
PRODUCT RECOMMENDATION 2	
	Mediterranean
	CLIMATE
	PRODUCT RECOMMENDATION 2  Gear Oil Alcat 30

## CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CP-563C 4LN00807 ->



(1995-2000)

ECCENTRIC WEIGHT HOUSING Capacity: 55 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Abacot MEP HD 220	
011	 -

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

FINAL DRIVE - DRUM Capacity: 3,2 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	
01 1 0 11 10 10 1	

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Abacot MEP Synth 220	

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

VIBRATORY SUPPORT Capacity: 0,85 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.