CATERPILLAR TRACKED EXCAVATORS 219 5CF (1987-1989)



ENGINE Capacity: 19 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	
Change every 250 hours/ 1 months	· · ·	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 250 hours/ 1 months	·	· ·
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 250 hours/ 1 months		· · · ·
FINAL DRIVES Capacity: 11,3 liter		
USE		CLIMATE
Normal		Mediterranean

 Normal
 Mediterranean

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2

 Multifleet SCD 50
 Multifleet SCD 40

Check every 1 months/ 250 hours

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Check every 1 months/ 250 hours	!

 USE
 CLIMATE

 Normal
 Arctic

 PRODUCT RECOMMENDATION 1
 Image: Climate state st

CATERPILLAR TRACKED EXCAVATORS 219 5CF (1987-1989)



HYDRAULIC SYSTEM Capacity: 155 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 3 months/ 500 hours, change	every 6 months/ 2000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
01 1 0 11 (500 1 1		

Check every 3 months/ 500 hours, change every 6 months/ 2000 hours

GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 27 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	
Change every 6 months/ 2000 hours	 -

CATERPILLAR TRACKED EXCAVATORS 219 5CF (1987-1989)



	CLIMATE
	Mediterranean
PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	
	CLIMATE
	Moderate
	CLIMATE
	Arctic

TRACK PINS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

TRACK ROLLERS & IDLERS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.