## CATERPILLAR TRACKED EXCAVATORS 312 6GK (1996-1998)



ENGINE 3064T Capacity: 13 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	
Change every 250 hours/ 1 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40
Change every 250 hours/ 1 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 250 hours/ 1 months		
FINAL DRIVES		
Capacity: 2,5 liter (each hub)		
use Normal		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1		Mediterranean
Gear Oil Alcat 50		
Check every 1 months/ 250 hours, change	eveny 12 months/2000 hours	
USE	every 12 months, 2000 nouns	CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

## CATERPILLAR TRACKED EXCAVATORS 312 6GK (1996-1998)



USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Change every 250 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 250 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours		
HYDRAULIC SYSTEM		
Capacity: 99 liter (Reservoir), Capacity: 15	1 liter (System)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 1 months/ 250 hours, change	every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	every 12 months/ 2000 hours	
GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

## CATERPILLAR TRACKED EXCAVATORS 312 6GK (1996-1998)



COOLING SYSTEM Capacity: 1,5 liter (Reservoir), Capacity: 15,5 liter (System)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 17				
Check every 1 months/ 250 hours, change	every 24 months/ 3000 hours			
SWING REDUCTION UNIT Capacity: 2,8 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 50				
Check every 1 months/250 hours, change	every 6 months/ 1000 hours			
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 30				
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours			
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 10W				
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours			
USE		CLIMATE		
Initial service		Mediterranean		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 50				
Change every 250 hours				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 30				

Change every 250 hours

## CATERPILLAR TRACKED EXCAVATORS 312 6GK (1996-1998)



CLIMATE

Illiliai Selvice		Aictic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change event 250 hours		<u> </u>
Change every 250 hours		
TRACK IDLERS		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
	-	
TRACK BOLLEDS		
TRACK ROLLERS		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
USE		CLIMATE
Normal		Moderate
		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
——————————————————————————————————————		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.