

| ENGINE C6.6 Acert Capacity: 23 liter | | |
|--------------------------------------|--------------------------|---------------|
| USE | | CLIMATE |
| Preferred | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agridiesel MSP 15W-40 | Dieselfleet MSP 15W-40 | |

Check every 10 hours, change every 3 months/ 500 hours

| USE | | CLIMATE |
|------------------------------|--------------------------|----------|
| Preferred | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Dieselfleet LSP Ultra 10W-30 | Dieselfleet MSP 10W-30 | |

Check every 10 hours, change every 3 months/ 500 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|---------------|
| Alternative (acceptable) | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrisynth MSP 10W-40 | Dieselfleet MSP 15W-40 | |

Check every 10 hours, change every 3 months/ 500 hours

| USE | | CLIMATE |
|------------------------------|--------------------------|------------------------------|
| Alternative (acceptable) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP Ultra FE 5W-30 | Agridiesel MSP 15W-40 | Dieselfleet LSP Ultra 10W-30 |

Check every 10 hours, change every 3 months/ 500 hours

| HYDRAULIC SYSTEM Capacity: 131 liter (Change capacity) | |
|--|---------------|
| USE | CLIMATE |
| Normal | Mediterranean |
| PRODUCT RECOMMENDATION 1 | |
| Gear Oil Alcat 30 | |

Check every 10 hours, change every 2000 hours/ 12 months

| 0/ / / / / | 20001 / 10 / 1 | |
|--------------------------|--------------------------|--------------------------|
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |
| USE | | CLIMATE |

Check every 10 hours, change every 2000 hours/ 12 months



| USE | | CLIMATE |
|---|--------------------------|--------------------------|
| Continuous hammer use | | climate Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |
| Check every 10 hours, change every 60 | 0 hours | |
| USE | | CLIMATE |
| Continuous hammer use | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |
| Check every 10 hours, change every 60 | 0 hours | |
| USE | | CLIMATE |
| Partial hammer use (50%) | _ | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |
| Check every 10 hours, change every 10 | 00 hours/ 12 months | |
| USE | | CLIMATE |
| Partial hammer use (50%) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |
| Check every 10 hours, change every 10 | 00 hours/ 12 months | |
| USE Diadagradable sil | | CLIMATE |
| Biodegradable oil | | Moderate |
| Perlus Biosynth 46 | | |
| <u> </u> | | |
| Check every 10 hours, change every 20 | 00 hours/ 12 months | |
| USE Piodogradable oil partial hammer | uso (50%) | climate Moderate |
| Biodegradable oil, partial hammer | use (50 %) | |
| Perlus Biosynth 46 | | |
| Check every 10 hours, change every 10 | 00 hours/12 months | |
| USE Check every 10 hours, change every 10 | OU HOURS/ 12 IHORRIS | CLIMATE |
| Biodegradable oil, full time hamme | er use (100%) | climate Moderate |
| | | |
| PRODUCT RECOMMENDATION 1 | | |
| | | |



| GREASE POINTS/NIPPLES | |
|--------------------------|----------|
| USE | CLIMATE |
| Alternative (acceptable) | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| HT Q9 High Grade Grease | |

| COOLING SYSTEM Capacity: 30 liter | |
|-----------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 17 | |

Check every 10 hours, change every 72 months/ 12000 hours

| SWING GEAR Capacity: 22 liter | | |
|----------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| Check every 12 months/ 2000 hour | S | , |



| SWING REDUCTION UNIT Capacity: 8 liter | | |
|---|----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |
| Check every 1 months/ 250 hours, change | every 6 months/ 1000 hours | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| Check every 1 months/ 250 hours, change | every 6 months/ 1000 hours | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |
| Change every 250 hours/ 6 months | | |
| USE | | CLIMATE |
| Initial service | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| Change every 250 hours/ 6 months | | |
| | | |
| TRACK IDLERS | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |
| | | |



| TRACK ROLLER FRAME PIVOT BEARIN | NGS | |
|---------------------------------|-----|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 50 | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| | | |
| TRACK ROLLER FRAME RECOIL SPRIN | NG | |
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 50 | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| | | |
| TRACK ROLLERS | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |
| | | |
| | | |



| TRAVEL REDUCTION UNIT Capacity: 10 liter (each) | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |
| Check every 1 months/ 250 hours, change every 12 months/ 2000 hours | | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| Check every 1 months/ 250 hours, change every 12 months/ 2000 hours | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |
| Change every 250 hours/ 6 months | | |
| USE | | CLIMATE |
| Initial service | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| Change every 250 hours/ 6 months | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.