

ENGINE 3116T Capacity: 21,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every 1 months/ 250 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Check every 10 hours, change every 1 months/ 250 hours

FINAL DRIVES Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours		

HYDRAULIC SYSTEM

Capacity: 141 liter (Hydraulic tank), Capacity: 265 liter (System)



use Normal		climate Mediterranean
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30		
Check every 10 hours, change every 2000	hours/ 12 months	
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra
Check every 10 hours, change every 2000	hours/ 12 months	· · · ·
use Up to 50% hammer use		climate Mediterranean
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30		
Check every 10 hours, change every 1000	hours/ 12 months	
use Up to 50% hammer use		climate Moderate
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra
Check every 10 hours, change every 1000	hours/ 12 months	
use Continuous hammer use		climate Mediterranean
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30		
Check every 10 hours, change every 600 l	nours/ 12 months	
use Continuous hammer use		climate Moderate
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra
Check every 10 hours, change every 600 l	hours/ 12 months	
GREASE POINTS/NIPPLES		
use Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 HT Q9 High Grade Grease	PRODUCT RECOMMENDATION 2	

Change every 10 hours



COOLING SYSTEM Capacity: 31,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	

Check every 10 hours, change every 72 months/ 6000 hours

SWING GEAR Capacity: 18,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 2000 hours/ 12 months

SWING REDUCTION UNIT Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

use Initial service		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Change every 250 hours

USE	CLIMATE
Initial service	Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Change every 250 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the



information contained herein is subject to changes without notification.