

JCB WHEELED LOADERS 411 HT JCB ECOMAX STAGE IIIB/T4I (2013-2016)



ENGINE JCB Ecomax T4i
Capacity: 14 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Armado Synth LSP Ultra 5W-30

PRODUCT RECOMMENDATION 3

Dieselfleet MSP 10W-30

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL FRONT JCB PD70
Capacity: 25 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT

Change every 500 hours

DIFFERENTIAL REAR JCB PD70
Capacity: 25 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT

Change every 500 hours

JCB WHEELED LOADERS 411 HT JCB ECOMAX STAGE IIIB/T4I (2013-2016)

**TRANSMISSION** ZF 4WG115 4/3

Capacity: 27 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 10 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 155 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Check every 10 hours, change every 2000 hours/ 24 months

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

COOLING SYSTEM

Capacity: 26 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.