

JCB WHEELED LOADERS 411 (1994-1999)**ENGINE** Perkins 1000T

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40*Change every 250 hours***DIFFERENTIAL FRONT**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Change every 500 hours***DIFFERENTIAL REAR**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Change every 500 hours***HUB REDUCTIONS FRONT**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Change every 500 hours***HUB REDUCTIONS REAR**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Change every 500 hours*

JCB WHEELED LOADERS 411 (1994-1999)**TRANSMISSION**

| USE | | CLIMATE |
|---------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 10W | ATF Dexron II-D | |

Change every 1000 hours

HYDRAULIC SYSTEM

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 46 | | |

Change every 2000 hours

HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 15 | | |

Change every 2000 hours

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| HT Q9 High Grade Grease | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.