PRODUCT RECOMMENDATION

JCB WHEELED LOADERS (USA) 417 HT USA JCB ECOMAX STAGE IIIB/T4I (2014 AND AFTER)

ENGINE JCB Ecomax T4i
Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth MSP 5W-40		

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL FRONT JCB PD70
Capacity: 25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Change every 500 hours

DIFFERENTIAL REAR JCB PD70
Capacity: 25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Change every 500 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

JCB WHEELED LOADERS (USA) 417 HT USA JCB ECOMAX STAGE IIIB/T4I (2014 AND AFTER)

TRANSMISSION ZF 4WG115 4/3
Capacity: 27 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 10 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM
Capacity: 155 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	**Perlus H 46**	

Check every 10 hours, change every 2000 hours/ 24 months

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	**Labora Grease**	

COOLING SYSTEM
Capacity: 26 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367