PRODUCT RECOMMENDATION

JCB ROUGH TERRAIN FORKLIFT TRUCKS 930 2WD JCB ECOMAX STAGE IIIB/T4I (2012 AND AFTER)

ENGINE JCB Ecomax T4i
Capacity: 15 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL FRONT
Capacity: 30 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

TRANSMISSION SynchroShuttle
Capacity: 17 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 10 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM
Capacity: 64 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	**Perlus AF 46**	

Check every 10 hours, change every 2000 hours/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	**Perlus AF 32**	

Check every 10 hours, change every 2000 hours/ 24 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

Check every 10 hours, change every 2000 hours/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

JCB ROUGH TERRAIN FORKLIFT TRUCKS 930 2WD JCB ECOMAX STAGE IIIB/T4I (2012 AND AFTER)

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	**Labora Grease**	

COOLING SYSTEM
Capacity: 14 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367