JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 540-170 USA (81 KW) STAGE IIIB/T4I (2014 AND AFTER)



ENGINE JCB Ecomax T4i Capacity: 15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Armado Synth MSP 5W-40	

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL FRONT Capacity: 17,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check avery 50 hours change avery 6 months/ 500 hours		

Check every 50 hours, change every 6 months/ 500 hours

DIFFERENTIAL REAR Capacity: 19 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 50 hours, change every 6 months/ 500 hours

CLIMATE
Moderate

Check every 50 hours, change every 6 months/ 500 hours

HUB REDUCTIONS REAR Capacity: 2 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check even 50 hours chapte even 6 menths/ 500 hours		

Check every 50 hours, change every 6 months/ 500 hours

JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 540-170 USA (81 KW) STAGE IIIB/T4I (2014 AND AFTER)



TRANSMISSION Synchro Shuttle SS700/750 Capacity: 11,5 liter (Change capacity), Capacity: 13,5 liter (Dry fill)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 1000 hours/ 12 months		
USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

Check every 10 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM Capacity: 180 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Check every 50 hours, change every 2000 hours/ 24 months		

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		
Check every 10 hours change every 2000	hours/24 months	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 540-170 USA (81 KW) STAGE IIIB/T4I (2014 AND AFTER)



Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Coolont CD 15	Coolort SD 42	Coolont 29 Organia NE
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
COOLING SYSTEM Capacity: 28 liter		

Check every 50 hours, change every 2000 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.