PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U KX91-2

ENGINE Kubota

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	**Multifleet SCD 50**

Check every 8 hours, change every 250 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Multifleet SCD 20W-20	**Multifleet SCD 10W**	

Check every 8 hours, change every 250 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	**Multifleet SCD 50**

Change every 50 hours

USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Multifleet SCD 20W-20	**Multifleet SCD 10W**	

Change every 50 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U KX91-2

HYDRAULIC SYSTEM
Capacity: 87 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 10 hours, change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 1000 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Perlus H 32		

Check every 10 hours, change every 1000 hours

COOLING SYSTEM
Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

Check every 10 hours, change every 24 months

PINS + BUSHINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Check every 8 hours

SWING REDUCTION UNIT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 1000 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U KX91-2

TRACK ROLLERS + FRONT IDLERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 1000 hours

TRAVEL REDUCTION UNIT
Capacity: 0,65-1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 500 hours/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 100 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367