## KUBOTA TRACKED CARRIERS KC/RC KC51D (2007 AND AFTER)



Change every 25 hours		
PRODUCT RECOMMENDATION 1  Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 3  Multifleet SHPD 10W-40
Initial service		Cold
USE		CLIMATE
Change every 25 hours		
Multifleet SCD 20W-20		
Initial service		Moderate
USE		CLIMATE
Change every 25 hours		
Multifleet SCD 30		
PRODUCT RECOMMENDATION 1		
use Initial service		climate Tropical
Check every 8 hours, change every 100	) hours	
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
use Normal		CLIMATE Cold
Check every 8 hours, change every 100	) hours	
Multifleet SCD 20W-20		
PRODUCT RECOMMENDATION 1		
Normal		Moderate
Check every 8 hours, change every 100	, 110ui s	CLIMATE
Multifleet SCD 30	) have	
PRODUCT RECOMMENDATION 1		
Normal		Tropical
USE		CLIMATE

## KUBOTA TRACKED CARRIERS KC/RC KC51D (2007 AND AFTER)



HYDRAULIC SYSTEM TILT MECHANISM Capacity: 1,5-1,9 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Perlus H 46				
Change every 500 hours				

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

TRAVEL REDUCTION UNIT Capacity: 1,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 300 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 50 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.