

MANITOU FORKLIFT TRUCKS MSI MSI 30 D BUGGIE SERIES 2-E2 PERKINS 404C-22 (2004-2008)



ENGINE Perkins 404C-22
Capacity: 9,75 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Check every 8 hours, change every 12 months/ 500 hours

AXLE OSCILLATION REAR

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Labora Grease

PRODUCT RECOMMENDATION 2
Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3
MP Lithep Grease EP 2

Change every 50 hours

HUB REDUCTIONS FRONT Brevini CWD 2050/1M
Capacity: 1 liter (each)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

Check every 50 hours, change every 2000 hours/ 24 months

HYDRAULIC SYSTEM

Capacity: 95 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Perlus H 46

Check every 50 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES MAST

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Q7 MP Calcep Grease WR 2

PRODUCT RECOMMENDATION 2
Caliplex HD Grease EP 2

PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2

Change every 50 hours

MANITOU FORKLIFT TRUCKS MSI MSI 30 D BUGGIE SERIES 2-E2 PERKINS 404C-22 (2004-2008)



GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

COOLING SYSTEM

Capacity: 10,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 8 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.