

MANITOU MANITRANSIT RANGE

TMD/TME/TMP/TMT/TMV TMT 55 HT-4W (T3)

KUBOTA V2403-M-E3B



ENGINE Kubota V2403-M-E3B
Capacity: 10,9 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3
Armado Synth 5W-30

Check every 10 hours, change every 500 hours/ 12 months

HYDRAULIC SYSTEM
Capacity: 45 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Perlus H 46

Check every 50 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES GENERAL

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
MoS2 Grease EP 2

COOLING SYSTEM
Capacity: 8 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Coolant SP 15+

PRODUCT RECOMMENDATION 2
Coolant SP 12

PRODUCT RECOMMENDATION 3
Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.