

MANITOU MANISCOPIC MLT MLT 629

TURBO SERIES A PERKINS 1004.4T (2001-2006)



ENGINE Perkins 1004.4T
Capacity: 7,75 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

Change every 400 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3
Armado Synth 5W-30

Change every 400 hours

USE
Initial service

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

Change every 50 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3
Armado Synth 5W-30

Change every 50 hours

ANGLE GEARBOX
Capacity: 2,25 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

Change every 800 hours

AXLE OSCILLATION REAR

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Labora Grease

PRODUCT RECOMMENDATION 2
Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3
MP Lithep Grease EP 2

MANITOU MANISCOPIC MLT MLT 629

TURBO SERIES A PERKINS 1004.4T (2001-2006)

**DIFFERENTIAL FRONT**

Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Change every 800 hours***DIFFERENTIAL REAR**

Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Change every 800 hours***HUB REDUCTIONS FRONT**

Capacity: 0,75 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 800 hours***HUB REDUCTIONS REAR**

Capacity: 0,75 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 800 hours***TRANSMISSION**

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Almirol*Change every 800 hours*

MANITOU MANISCOPIC MLT MLT 629

TURBO SERIES A PERKINS 1004.4T (2001-2006)



HYDRAULIC SYSTEM

Capacity: 125 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 800 hours

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 23,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

SLIDING PADS JIB

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.