MANITOU MANISCOPIC MRT MRT 1640 E3 PERKINS 1104D-44T



ENGINE Perkins 1104D-44T Capacity: 7 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 500 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40

Check every 10 hours, change every 500 hours/ 12 months

Check every 250 hours, change every 1000 hours/12 months

DIFFERENTIAL FRONT Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 250 hours, change every	1000 hours/ 12 months	

DIFFERENTIAL REAR Capacity: 11 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

HUB REDUCTIONS FRONT Capacity: 1,6 liter (each hub)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT			
Check every 250 hours, change eve	v 1000 hours/ 12 months		

MANITOU MANISCOPIC MRT MRT 1640 E3 PERKINS 1104D-44T



HUB REDUCTIONS REAR Capacity: 1,6 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
01 1 0501 1 100	0.0	

Check every 250 hours, change every 1000 hours/ 12 months

TRANSMISSION HYDROSTATIC 2/2 Capacity: 2,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
	-

Check every 250 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM Capacity: 150 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Check every 50 hours, change every 1000	s/ 12 months	

GREASE POINTS/NIPPLES BEARINGS SLEWING GEAR			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
MoS2 Grease EP 2			

GREASE POINTS/NIPPLES GENERAL		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	
Change every 50 hours	'	'

MANITOU MANISCOPIC MRT MRT 1640 E3 PERKINS 1104D-44T



GREASE POINTS/NIPPLES TELESCOPIC BOOM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Change every 50 hours		

COOLING SYSTEM Capacity: 18 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

SWING REDUCTION UNIT Capacity: 2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Abacot MEP HD 150	Abacot MEP 150	
Check every 250 hours, change ev	ery 1000 hours/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149 7600 AC Almelo