

ACURA (USA / CAN) NSX NC1 NSX (CAN) (2016-2022)

**ENGINE JNC1**

Capacity: 7,9 liter (Service fill), Filter capacity: 0,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL FRONT Twin Motor Unit

Capacity: 2,42 liter

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Change every 24000 km

USE		CLIMATE
First change only, severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Change every 12000 km

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

TRANSMISSION AUTOMATIC DCT CLUTCH PART M8HF 9/1

Capacity: 2,6 liter

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Change every 32000 km

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

TRANSMISSION AUTOMATIC DCT TRANSMISSION PART M8HF 9/1

Capacity: 4,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

ACURA (USA / CAN) NSX NC1 NSX (CAN) (2016-2022)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid Racing		

Change every 36 months

COOLING SYSTEM

Capacity: 15,5 liter

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

COOLING SYSTEM INVERTER

Capacity: 1,9 liter

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.