

ALFA ROMEO (EU) SPIDER 916 SPIDER 2.0 JTS (2003-2006)



ENGINE 2.0 Direct
Capacity: 4,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Emperol Racing 10W-60*Change every 20000 km*

TRANSAXLE MANUAL 5/1
Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Syngear 75W-90*Check every 80000 km/ 48 months*

HYDRAULIC SYSTEM (ROOF) ELECTRONIC/HYDRAULIC
Capacity: 0,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013*Check every 20000 km/ 12 months*

HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0,45 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 500 km, change every 60000 km/ 24 months*

POWER STEERING

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 500 km*

ALFA ROMEO (EU) SPIDER 916 SPIDER 2.0 JTS (2003-2006)

**COOLING SYSTEM**

Capacity: 8,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Check every 500 km, change every 60000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.