

AUDI (EU) 80, RS 2 80 1.8 (1990-1991)**MOTORE**

Capacità: 3 litro, Capacità filtro: 0,5 litro

USO	CLIMA
Normale	Moderato

CONSIGLI PRODOTTO 1	CONSIGLI PRODOTTO 2	CONSIGLI PRODOTTO 3
Helar SP LL-03 5W-30	Specialsynth MSP 5W-40	Emperol 5W-40

Cambiare ogni 15000 km/ 12 mesi

USO	CLIMA
Normale	Artico

CONSIGLI PRODOTTO 1		
Presteza MSP 5W-30		

*Cambiare ogni 15000 km/ 12 mesi***DIFFERENZIALE DA AUTOMATICO**

Capacità: 0,75 litro

USO	CLIMA
Normale	Moderato

CONSIGLI PRODOTTO 1	CONSIGLI PRODOTTO 2	
SP Gear 1011	Syngear TDL 75W-90	

*Controllare ogni 30000 km***TRANSAXLE MANUALE 4/1**

Capacità: 2,35 litro

USO	CLIMA
Normale	Moderato

CONSIGLI PRODOTTO 1	CONSIGLI PRODOTTO 2	
SP Gear 1011	Syngear TDL 75W-90	

*Controllare ogni 15000 km/ 12 mesi***TRASMISSIONE AUTOMATICA 3/1**

Capacità: 3 litro

USO	CLIMA
Normale	Moderato

CONSIGLI PRODOTTO 1		
ATF Dexron II-D		

Controllare ogni 30000 km/ 12 mesi, cambiare ogni 60000 km

**IMPIANTI FRENI IDRAULICI**

USO		CLIMA
Normale		Moderato
CONSIGLI PRODOTTO 1	CONSIGLI PRODOTTO 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Cambiare ogni 24 mesi

SERVOSTERZO

USO		CLIMA
Normale		Moderato
CONSIGLI PRODOTTO 1		
SP Fluid 3013		

IMPIANTO DI RAFFREDDAMENTO

Capacità: 8,5 litro

USO		CLIMA
Normale		Moderato
CONSIGLI PRODOTTO 1		
Coolant -38 Organic NF		

Cambiare ogni 24 mesi

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.