

AUDI (EU) 80, RS 2 80 1.9 D (1990-1991)**MOTORE**

Capacità: 3,5 litro, Capacità filtro: 0,5 litro

USO		CLIMA
Normale		Moderato
CONSIGLI PRODOTTO 1	CONSIGLI PRODOTTO 2	CONSIGLI PRODOTTO 3
Specialsynth MSP 5W-40	Emperol 5W-40	Emperol 10W-40

*Cambiare ogni 7500 km/ 12 mesi***TRANSAXLE MANUALE 5/1**

USO		CLIMA
Normale		Moderato
CONSIGLI PRODOTTO 1	CONSIGLI PRODOTTO 2	
SP Gear 1011	Syngear TDL 75W-90	

IMPIANTI FRENI IDRAULICI

USO		CLIMA
Normale		Moderato
CONSIGLI PRODOTTO 1	CONSIGLI PRODOTTO 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Cambiare ogni 24 mesi***SERVOSTERZO**

USO		CLIMA
Normale		Moderato
CONSIGLI PRODOTTO 1		
SP Fluid 3013		

IMPIANTO DI RAFFREDDAMENTO

Capacità: 6,5 litro

USO		CLIMA
Normale		Moderato
CONSIGLI PRODOTTO 1		
Coolant -38 Organic NF		

Cambiare ogni 24 mesi

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.