

MAN TGL EURO 5 TGL 8.150 BB/BL (4X2)

EURO 5 EEV (2010 AND AFTER)



ENGINE D 0834 LFL60/Euro 5 EEV
Capacity: 16,5 liter, Filter capacity: 1,5 liter

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 80000 km/ 12 months

USE	CLIMATE
Distribution, fuel 15-25 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 42000 km/ 12 months

USE	CLIMATE
Regional, fuel < 15 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 60000 km/ 12 months

USE	CLIMATE
Severe, fuel >25 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 24000 km/ 12 months

DIFFERENTIAL REAR HY-0718
Capacity: 5,25 liter

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 300000 km/ 36 months

USE	CLIMATE
Extended, tropical climate	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 36 months

MAN TGL EURO 5 TGL 8.150 BB/BL (4X2) EURO 5 EEV (2010 AND AFTER)



USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 24 months

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 125000 km/ 24 months

USE		CLIMATE
Tropical climate		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 130000 km/ 24 months

USE		CLIMATE
Alternative (acceptable), tropical climate		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 80000 km/ 24 months

TRANSMISSION MANUAL ZF 6S-800 TO 6/1 Capacity: 9,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 240000 km/ 24 months

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear HS 75W-90

Change every 120000 km/ 12 months

MAN TGL EURO 5 TGL 8.150 BB/BL (4X2)

EURO 5 EEV (2010 AND AFTER)

**HYDRAULIC CAB TILT SYSTEM**

Capacity: 0,5-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

HYDRAULIC CLUTCH SYSTEM

Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

POWER STEERING ZF Servocom

Capacity: 2-3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

CENTRAL LUBRICATION SYSTEM BEKA-MAX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

CENTRAL LUBRICATION SYSTEM OIL Vogel

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

MAN TGL EURO 5 TGL 8.150 BB/BL (4X2)

EURO 5 EEV (2010 AND AFTER)



GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

WHEEL BEARINGS REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 500000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.