ATLAS GMBH WHEELED LOADERS 4WD 82E DEUTZ BF4L-1011 (1994-2002)



ENGINE Deutz BF4L-1011		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 250 hours/ 3 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 50 hours		
DIFFERENTIAL FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 1500 hours/ 12 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 500 hours		
DIFFERENTIAL REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 1500 hours/ 12 months		
USE		CLIMATE

KROON-OIL B.V. Postbus 149 7600 AC Almelo

Initial service

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 500 hours

Moderate

ATLAS GMBH WHEELED LOADERS 4WD 82E DEUTZ BF4L-1011 (1994-2002)



HUB REDUCTIONS FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 1500 hours/ 12 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 500 hours		
IIIID DEDUCTIONS DE LE		
HUB REDUCTIONS REAR		
use Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1		Woderate
Gearlube LS 80W-90		
Change every 1500 hours/ 12 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 500 hours		
HYDRAULIC SYSTEM HYDROSTATIC D	RIVE	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1 Perlus H 46		
Change every 12 months USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Change every 1500 hours		

ATLAS GMBH WHEELED LOADERS 4WD 82E DEUTZ BF4L-1011 (1994-2002)



HYDRAULIC BRAKE SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
ATF Dexron II-D				
Change every 1500 hours/ 12 months				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				
ATF Dexron II-D				
Change every 500 hours				
GREASE POINTS/NIPPLES				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
MoS2 Grease EP 2				
ANTI-FRICTION BEARINGS				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
MoS2 Grease EP 2				
PLAIN BEARINGS				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

MoS2 Grease EP 2