PRODUCT RECOMMENDATION

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR60 DEUTZ TD 2009 L04 (2008-2012)

ENGINE Deutz TD 2009 L04
Capacity: 5,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		

Check every 8 hours, change every 12 months/ 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	**Agrisynth MSP 10W-40**	**Agridiesel MSP 15W-40**

Check every 8 hours, change every 12 months/ 500 hours

DIFFERENTIAL FRONT
Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 500 hours, change every 12 months/ 1500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 500 hours

DIFFERENTIAL REAR
Capacity: 5,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 500 hours, change every 12 months/ 1500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 500 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR60 DEUTZ TD 2009 L04 (2008-2012)

HUB REDUCTIONS FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 500 hours, change every 12 months/ 1500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 500 hours

HUB REDUCTIONS REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 500 hours, change every 12 months/ 1500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 500 hours

TRANSMISSION
Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 500 hours, change every 12 months/ 1500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 500 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR60 DEUTZ TD 2009 L04 (2008-2012)

HYDRAULIC SYSTEM
Capacity: 60 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	**Perlus H 46**	

Check every 8 hours, change every 24 months/ 3000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	**Perlus H 46**	

Change every 1500 hours

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 8 hours, change every 24 months/ 3000 hours

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Change every 1500 hours/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Change every 500 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM
Capacity: 4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR60 DEUTZ TD 2009 L04 (2008-2012)

Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367