

ATLET LOW LEVEL ORDER PICKERS

TEMPO PPD



TRANSMISSION

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 800 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 800 hours

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 500 hours

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 500 hours

ATLET LOW LEVEL ORDER PICKERS

TEMPO PPD



HYDRAULIC SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32*Change every 800 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Perlus H 15*Change every 800 hours*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32*Change every 500 hours*

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1

Perlus H 15*Change every 500 hours*

GREASE POINTS/NIPPLES LIFT CHAIN

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Industrial Chain Spray

GREASE POINTS/NIPPLES MAST BEARINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

ATLET LOW LEVEL ORDER PICKERS

TEMPO PPD



GREASE POINTS/NIPPLES MAST CHAINS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

GREASE POINTS/NIPPLES STEERING CHAINS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.