

# ATLET STACKERS/PICKERS TERGO UND 120 (2011 AND AFTER)



## TRANSMISSION

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 3000 hours*

## USE

Cold store (stay-in &amp; in-out)

## CLIMATE

Arctic

## PRODUCT RECOMMENDATION 1

**SP Gear 1011**

## PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90***Change every 3000 hours*

## TRANSMISSION ZF

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90***Change every 3000 hours*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1011**

## PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90***Change every 3000 hours*

# ATLET STACKERS/PICKERS TERGO UND 120 (2011 AND AFTER)



## HYDRAULIC SYSTEM

Capacity: 37 liter

| USE                       |                          | CLIMATE  |
|---------------------------|--------------------------|----------|
| Normal                    |                          | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus Biosynth 32</b> | <b>Perlus H 32</b>       |          |

Check every 10 hours, change every 3000 hours

| USE                           |  | CLIMATE |
|-------------------------------|--|---------|
| Cold store (stay-in & in-out) |  | Arctic  |
| PRODUCT RECOMMENDATION 1      |  |         |
| <b>SP Fluid 3013</b>          |  |         |

Check every 10 hours, change every 3000 hours

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Biodegradable oil         |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Perlus Biosynth 32</b> |  |          |

Check every 10 hours, change every 3000 hours

## GREASE POINTS/NIPPLES

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.