### AUSA MULTITASK B400H 4X4



ENGINE Volkswagen TDI 2.0 Capacity: 4,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Helar SP LL-03 5W-30		
Charle avery 10 hours shares avery 200 h	aura/12 months	

Check every 10 hours, change every 300 hours/ 12 months

DIFFERENTIAL FRONT Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 600 hours, change every 1800 hours

DIFFERENTIAL REAR Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 600 hours, change every 1800 hours

#### TRANSFERBOX 4WD "FullGrip" Capacity: 1,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## AUSA MULTITASK B400H 4X4



HYDRAULIC SYSTEM Capacity: 75 liter			
USE		CLIMATE	
Normal		Tropical	
PRODUCT RECOMMENDATION 1			
Perlus H 68			
Check every 10 hours, change every	/ 1800 hours		
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 46	Perlus H 46		
Check every 10 hours, change every	/ 1800 hours		
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 32	Perlus H 32		
Check every 10 hours, change every	/ 1800 hours		
HYDRAULIC BRAKE SYSTEM			

Capacity: 0,25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 12 months/ 300 hours, change every 1800 hours

#### **GREASE POINTS/NIPPLES**

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12	
Check every 12 months/ 600 hours	

# AUSA MULTITASK B400H 4X4



HIGH PRESSURE PUMP Capacity: 0,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
0k		!	

Change every 900 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.