PRODUCT RECOMMENDATION

# AUSA MULTITASK M300H

| **ENGINE** Volkswagen TDI 2.0<br>Capacity: 4,5 liter | | |
|---|---|---|
| USE<br>Normal | | CLIMATE<br>Moderate |
| PRODUCT RECOMMENDATION 1<br>**Helar SP LL-03 5W-30** | | |
| *Change every 12 months/ 150 hours* | | |
| USE<br>Initial service | | CLIMATE<br>Moderate |
| PRODUCT RECOMMENDATION 1<br>**Helar SP LL-03 5W-30** | | |
| *Change every 50 hours* | | |

| **DIFFERENTIAL FRONT**<br>Capacity: 2,5 liter | | |
|---|---|---|
| USE<br>Normal | | CLIMATE<br>Moderate |
| PRODUCT RECOMMENDATION 1<br>**Gearlube GL-5 80W-90** | PRODUCT RECOMMENDATION 2<br>**Unigear HS GL-3/GL-5 80W-90** | |
| *Change every 900 hours* | | |
| USE<br>Initial service | | CLIMATE<br>Moderate |
| PRODUCT RECOMMENDATION 1<br>**Gearlube GL-5 80W-90** | PRODUCT RECOMMENDATION 2<br>**Unigear HS GL-3/GL-5 80W-90** | |
| *Change every 50 hours* | | |

| **DIFFERENTIAL REAR**<br>Capacity: 2,5 liter | | |
|---|---|---|
| USE<br>Normal | | CLIMATE<br>Moderate |
| PRODUCT RECOMMENDATION 1<br>**Gearlube GL-5 80W-90** | PRODUCT RECOMMENDATION 2<br>**Unigear HS GL-3/GL-5 80W-90** | |
| *Change every 900 hours* | | |
| USE<br>Initial service | | CLIMATE<br>Moderate |
| PRODUCT RECOMMENDATION 1<br>**Gearlube GL-5 80W-90** | PRODUCT RECOMMENDATION 2<br>**Unigear HS GL-3/GL-5 80W-90** | |
| *Change every 50 hours* | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# AUSA MULTITASK M300H

## TRANSFERBOX Compen
Capacity: 1,5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Gearlube LS 80W-90** | | |

*Change every 600 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Gearlube LS 80W-90** | | |

*Change every 50 hours*

## HYDRAULIC SYSTEM
Capacity: 75 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Perlus Biosynth 46** | **Perlus H 46** | |

*Change every 900 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Perlus Biosynth 46** | **Perlus H 46** | |

*Change every 50 hours*

## HYDRAULIC BRAKE SYSTEM
Capacity: 0,25 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | |

*Check every 40 hours, change every 900 hours*

## GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# AUSA MULTITASK M300H

| COOLING SYSTEM<br>Capacity: 15 liter | | |
|---|---|---|
| USE<br>Normal | | CLIMATE<br>Moderate |
| PRODUCT RECOMMENDATION 1<br>**Coolant SP 12** | | |
| *Check every 10 hours, change every 1800 hours* | | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367