

# BARFORD SITE DUMPERS SXR3500

## HYDRO KUBOTA (2007 AND AFTER)

**ENGINE** Kubota V2203-M

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 500 hours*

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20***Change every 500 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 10W-40***Change every 500 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Change every 500 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Tropical |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 50 hours*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20***Change every 50 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 10W-40***Change every 50 hours*

# BARFORD SITE DUMPERS SXR3500

## HYDRO KUBOTA (2007 AND AFTER)



| USE                          |  | CLIMATE |
|------------------------------|--|---------|
| Initial service              |  | Arctic  |
| PRODUCT RECOMMENDATION 1     |  |         |
| <b>Multifleet SCD 10W</b>    |  |         |
| <i>Change every 50 hours</i> |  |         |

| DIFFERENTIAL FRONT<br>Capacity: 3,6 liter |                                    |          |
|-------------------------------------------|------------------------------------|----------|
| USE                                       |                                    | CLIMATE  |
| Normal                                    |                                    | Moderate |
| PRODUCT RECOMMENDATION 1                  | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b>               | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |
| <i>Change every 1000 hours</i>            |                                    |          |

| DIFFERENTIAL REAR<br>Capacity: 3,5 liter |                                    |          |
|------------------------------------------|------------------------------------|----------|
| USE                                      |                                    | CLIMATE  |
| Normal                                   |                                    | Moderate |
| PRODUCT RECOMMENDATION 1                 | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b>              | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |
| <i>Change every 1000 hours</i>           |                                    |          |

| TRANSFERBOX<br>Capacity: 0,57 liter |                                    |          |
|-------------------------------------|------------------------------------|----------|
| USE                                 |                                    | CLIMATE  |
| Normal                              |                                    | Moderate |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b>         | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |
| <i>Change every 1000 hours</i>      |                                    |          |

| HYDRAULIC SYSTEM<br>Capacity: 40 liter |                          |          |
|----------------------------------------|--------------------------|----------|
| USE                                    |                          | CLIMATE  |
| Normal                                 |                          | Moderate |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 46</b>                     | <b>Perlus AF 46</b>      |          |
| <i>Change every 1000 hours</i>         |                          |          |



# BARFORD SITE DUMPERS SXR3500

## HYDRO KUBOTA (2007 AND AFTER)



### HYDRAULIC BRAKE SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Perlus H 15</b>       |  |          |

### GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

### COOLING SYSTEM

| USE                           |  | CLIMATE  |
|-------------------------------|--|----------|
| Normal                        |  | Moderate |
| PRODUCT RECOMMENDATION 1      |  |          |
| <b>Coolant -38 Organic NF</b> |  |          |

*Change every 1000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*