

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25DN MK 6.3 (6X6) MERCEDES-BENZ OM906LA (STAGE



ENGINE Mercedes-Benz OM906LA
Capacity: 29 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-----------------------------|----------------------------|
| Agrisynth LSP 10W-40 | Armado Synth 10W-40 |

Change every 500 hours

DIFFERENTIAL FRONT 14R8E
Capacity: 30 liter (Dry fill), Capacity: 29 liter (Service fill)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|-------------------------------------|--|--|
| Unigear LS GL-3/GL-5 85W-140 | | |

Check every 500 hours, change every 1000 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

Check every 500 hours, change every 1000 hours

DIFFERENTIAL MIDDLE 14R8F
Capacity: 27 liter (Dry fill), Capacity: 26 liter (Service fill)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|-------------------------------------|--|--|
| Unigear LS GL-3/GL-5 85W-140 | | |

Check every 500 hours, change every 1000 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

Check every 500 hours, change every 1000 hours

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25DN MK 6.3 (6X6) MERCEDES-BENZ OM906LA (STAGE

**DIFFERENTIAL REAR 14R8E**

Capacity: 29 liter (Dry fill), Capacity: 28 liter (Service fill)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|-------------------------------------|--|--|
| Unigear LS GL-3/GL-5 85W-140 | | |

Check every 500 hours, change every 1000 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

*Check every 500 hours, change every 1000 hours***FINAL DRIVES**

Capacity: 4 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|-------------------------------------|--|--|
| Unigear LS GL-3/GL-5 85W-140 | | |

Check every 500 hours, change every 1000 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

*Check every 500 hours, change every 1000 hours***TRANSFERBOX VGR 13100**

Capacity: 4,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Matic 2032 | | |

Change every 2000 hours

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25DN MK 6.3 (6X6) MERCEDES-BENZ OM906LA (STAGE

**TRANSMISSION** Allison 3000P ORS 6/1

Capacity: 36 liter (Dry fill), Capacity: 24 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 2000 hours***TRANSMISSION** ZF 6HP592C 6/1

Capacity: 30 liter (Dry fill), Capacity: 10-15 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 1000 hours***HYDRAULIC SYSTEM**

Capacity: 120 liter (Hydraulic system including tank), Capacity: 85 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

PRODUCT RECOMMENDATION 2

Multifleet SCD 10W*Change every 3000 hours***GREASE POINTS/NIPPLES**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2**COOLING SYSTEM**

Capacity: 28 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.