

# BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25L MK II (4X4) MERCEDES-BENZ OM906LA (TIER 2)



**ENGINE** Mercedes-Benz OM906LA  
Capacity: 38 liter (Dry fill), Capacity: 29 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agrisynth LSP 10W-40</b>	<b>Armado Synth 10W-40</b>

*Change every 500 hours*

## DIFFERENTIAL FRONT Bell

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	
<b>Gear Oil Alcat 50</b>	

*Check every 1000 hours, change every 2000 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	
<b>Gear Oil Alcat 50</b>	

*Change every 100 hours*

## DIFFERENTIAL REAR Bell

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	
<b>Gear Oil Alcat 50</b>	

*Check every 1000 hours, change every 2000 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	
<b>Gear Oil Alcat 50</b>	

*Change every 100 hours*

# BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25L MK II (4X4) MERCEDES-BENZ OM906LA (TIER 2)

**TRANSMISSION** ZF 6WG210 6/3

Capacity: 26 liter (Dry fill), Capacity: 16 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032***Change every 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032***Change every 100 hours***HYDRAULIC SYSTEM**

Capacity: 85 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus H 46**

PRODUCT RECOMMENDATION 2

**Perlus H 68**

PRODUCT RECOMMENDATION 3

**Perlus AF 46***Change every 4000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Almirol**

PRODUCT RECOMMENDATION 3

**Perlus H 32***Change every 4000 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2****COOLING SYSTEM**

Capacity: 28 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12***Change every 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

PRODUCT RECOMMENDATION

**BELL EQUIPMENT ARTICULATED DUMP  
TRUCKS B-C-D-E SERIES B25L MK II (4X4)  
MERCEDES-BENZ OM906LA (TIER 2)**



*Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*