

CASE BACKHOE LOADERS 590 TURBO

**ENGINE**

Capacity: 11 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agridiesel MSP 15W-40****PRODUCT RECOMMENDATION 2****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 3****Dieselfleet CD+ 15W-40***Check every 10 hours, change every 250 hours***USE**

Normal

CLIMATE

Cold

PRODUCT RECOMMENDATION 1**Synfleet SHPD 10W-40****PRODUCT RECOMMENDATION 2****Multifleet SHPD 10W-40***Check every 10 hours, change every 250 hours***TRANSAXLE**

Capacity: 45 liter (Change capacity), Capacity: 54 liter (Total)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 2****Agrifluid HT-Plus****PRODUCT RECOMMENDATION 3****Agrifluid HT***Check every 250 hours, change every 1000 hours***HYDRAULIC SYSTEM**

Capacity: 79,5 liter (Hydraulic tank), Capacity: 128,7 liter (Total)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 2****Agrifluid HT-Plus***Check every 50 hours, change every 1000 hours***USE**

Biodegradable oil

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Perlus Biosynth 46***Check every 50 hours, change every 1000 hours*

CASE BACKHOE LOADERS 590 TURBO



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 10 hours

COOLING SYSTEM

Capacity: 17,8 liter, Capacity: 18,5 liter (+ heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.