PRODUCT RECOMMENDATION

# CASE MINI EXCAVATORS CK/CX CX50 MITSUBISHI 4N-EID (2002-2004)

## ENGINE Mitsubishi 4N-EID
Capacity: 7,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Agridiesel CRD+ 15W-40** | **Multifleet SHPD 15W-40** | |

*Check every 10 hours, change every 250 hours*

| USE | CLIMATE |
|---|---|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Kroontrak MTH 10W-30** | **Asyntho 5W-30** | **Armado Synth 5W-30** |

*Check every 10 hours, change every 250 hours*

## HYDRAULIC SYSTEM
Capacity: 68 liter (Hydraulic tank), Capacity: 100 liter (Total)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Agrifluid Synth XHP Ultra** | **Agrifluid HT-Plus** | |

*Check every 10 hours, change every 2000 hours*

| USE | CLIMATE |
|---|---|
| Biodegradable oil | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Perlus Biosynth 46** | | |

*Check every 10 hours, change every 2000 hours*

## GREASE POINTS/NIPPLES

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **MoS2 Grease EP 2** | | |

*Change every 50 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CASE MINI EXCAVATORS CK/CX CX50 MITSUBISHI 4N-EID (2002-2004)

## COOLING SYSTEM
Capacity: 9,8 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Coolant -38 Organic NF** | **Coolant -26** | |

*Check every 10 hours, change every 1000 hours*

## GEAR REDUCTION UNIT
Capacity: 1,7 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 250 hours, change every 2000 hours*

## SWING RING GEAR TEETH

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **MoS2 Grease EP 2** | | |

*Change every 250 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367