

CASE TRACKED EXCAVATORS CX CX130

CASE 4T-390 (2001-2008)



ENGINE Case 4T-390
Capacity: 9,5 liter (Crankcase)

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SHPD 20W-50

Check every 10 hours, change every 500 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours

USE
Normal

CLIMATE
Cold

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 10W-40

Check every 10 hours, change every 500 hours

HYDRAULIC SYSTEM

Capacity: 123 liter (Circuit), Capacity: 7 liter (Oil cooler), Capacity: 73 liter (Oil tank)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Perlus H 46

PRODUCT RECOMMENDATION 2
Perlus H 22

Check every 10 hours, change every 5000 hours

GREASE POINTS/NIPPLES

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
MoS2 Grease EP 2

Change every 10 hours

CASE TRACKED EXCAVATORS CX CX130

CASE 4T-390 (2001-2008)

**COOLING SYSTEM**

Capacity: 17,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

*Check every 10 hours, change every 24 months***SWING REDUCTION UNIT**

Capacity: 2,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

*Change every 250 hours***TRAVEL REDUCTION UNIT**

Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.