PRODUCT RECOMMENDATION

CASE SKID STEER LOADERS SR250 (2012-2017)

ENGINE Case 434T/E Tier 4
Capacity: 9,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Armado Synth 5W-30**	**Dieselfleet LSP Ultra 10W-30**

Check every 10 hours, change every 250 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Armado Synth 5W-30**	**Dieselfleet LSP Ultra 10W-30**

Change every 50 hours

CHAIN DRIVE UNIT
Capacity: 27,9 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak MTH 10W-30	**Armado Synth 5W-30**	**Dieselfleet LSP Ultra 10W-30**

Check every 500 hours, change every 1000 hours

HYDRAULIC SYSTEM
Capacity: 15 liter (Hydraulic tank), Capacity: 44,5 liter (System)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak MTH 10W-30	**Armado Synth 5W-30**	**Dieselfleet LSP Ultra 10W-30**

Check every 10 hours, change every 1000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Change every 10 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CASE SKID STEER LOADERS SR250 (2012-2017)

COOLING SYSTEM
Capacity: 19 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

Check every 10 hours, change every 1000 hours

TRAVEL REDUCTION UNIT
Capacity: 1 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	**Unigear LS GL-3/GL-5 85W-140**	

Change every 500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	**Unigear LS GL-3/GL-5 85W-140**	

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367