CASE WHEELED LOADERS 621D XT CASE 668TA/M2 (2003-2007)



ENGINE Case 668TA/M2 Capacity: 16,1 liter		
use Normal		
		PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40		

Change every 500 hours

DIFFERENTIAL FRONT ZF Capacity: 20,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 1000 hours		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 500 hours		

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Agrifluid HT	
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Agrifluid HT	
•	
	Agrifluid HT PRODUCT RECOMMENDATION 2

CASE WHEELED LOADERS 621D XT CASE 668TA/M2 (2003-2007)



HUB REDUCTIONS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 1000 hours		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 500 hours		

TRANSMISSION POWERSHIFT ZF 4/3 Capacity: 18,9 liter (Change capacity), Capacity: 26 liter (Dry fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT-Plus			
Change every 1000 hours			

HYDRAULIC SYSTEM Capacity: 68,5 liter (Hydraulic tank), Capacity: 113,6 liter (Total)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Change every 2000 hours		

COOLING SYSTEM Capacity: 34,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 10 hours, change ever	v 2000 hours/24 months		

Check every 10 hours, change every 2000 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.