

# CASE WHEELED LOADERS 821B CASE 6T-830 (1994-1999)



**ENGINE** Case 6T-830  
Capacity: 20,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agridiesel CRD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Asyntho 5W-30</b>	<b>Armado Synth 5W-30</b>

*Check every 10 hours, change every 250 hours*

**DIFFERENTIAL FRONT**  
Capacity: 18,9 liter, Capacity: 1,9 liter (LS-additive)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Unigear LS GL-3/GL-5 85W-140</b>		

*Change every 1000 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1		
<b>Unigear LS GL-3/GL-5 85W-140</b>		

*Change every 100 hours*

**DIFFERENTIAL REAR**  
Capacity: 13,4 liter, Capacity: 1,4 liter (LS-additive)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Unigear LS GL-3/GL-5 85W-140</b>		

*Change every 1000 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1		
<b>Unigear LS GL-3/GL-5 85W-140</b>		

*Change every 100 hours*

# CASE WHEELED LOADERS 821B CASE 6T-830 (1994-1999)



## HUB REDUCTIONS

Capacity: 6,2 liter (Front), Capacity: 5,7 liter (Rear)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

*Change every 1000 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

*Change every 100 hours*

## TRANSMISSION POWERSHIFT ZF 4WG200 4/3

Capacity: 12,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Check every 50 hours, change every 1000 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

*Check every 50 hours, change every 1000 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Check every 50 hours, change every 100 hours*

USE	CLIMATE
First change only	Arctic

PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

*Check every 50 hours, change every 100 hours*

# CASE WHEELED LOADERS 821B CASE 6T-830 (1994-1999)



## HYDRAULIC SYSTEM

Capacity: 90 liter (Hydraulic tank), Capacity: 174 liter (Total)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>

*Check every 50 hours, change every 2000 hours*

## COOLING SYSTEM

Capacity: 39 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10 hours, change every 2000 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*